Short Jacket - Выкройка #2477

Recommendations on fabric: thin coat or natural/mixed suiting fabrics.



You will also need: fusible interfacing, decorative closure.

Seam allowances: all seams 1 cm. Seam allowance along the lower edge on back and on side front – 2.5 cm.

О припусках на швы::
- Если на выкройке двойной контур, припуски на швы уже включены. Они составляют 1 см, если не указано иначе.
- Если у выкройки одинарный контур, припуски на швы не включены, и должны быть добавлены при раскрое.

О требуемой длине ткани:
Внимание! В инструкциях не указано необходимое количество ткани, так как оно зависит от ширины и рисунка ткани, а также Ваших размерных признаков. Прежде всего, распечатайте лекала и разложите их на ширине, соответствующей ширине ткани, которую Вы хотите использовать (обычно от 90 до 150 см), чтобы определить, сколько ткани Вам потребуется. Не забывайте учитывать парные детали и детали со сгибом.

РАСКРОЙ:

Обратите внимание при раскрое:
Обратите внимание на обозначение долевой нити при раскладке деталей. Некоторые детали кроятся со сгибом. Это указано на лекале. Перенесите все отметки и другие особенности дизайна (вытачки и т.п.) с лекала на ткань.
При стачивании деталей, обращайте внимание на надсечки, они должны совпадать.

Main fabric:
1. Back - cut 2
2. Side front – cut 2
3. Center front – cut 4
4. Cuff – cut 2

Fusible interfacing:
1. Center front – cut 2

2. Cuff – cut 2

Инструкции:

1. Apply fusible interfacing.

2. Sew center back seam. Serge seam and press towards left.

3. Sew upper edge of sleeve. Serge seams and press towards back.

4. Sew side seams and sleeve seams. Serge seams and press towards back.

5. Serge the seam allowance along the hem, turn inside and topstitch.(or finish with hidden stitches).

6. Pin center fronts together, right sides together and sew center collar seam. Press the seam allowances apart. Pin center pieces together, right sides together and sew center front edge and lower edges. Clip seam allowances, trim away corners. Pin the outer side of the center piece onto garment and sew along the center front edge and the neckline. Fold inside the seam allowance of the inner part and topstitch into seam of.

7. Sew cuff into a ring. Press the seam allowances apart. Pin the cuff onto sleeve, right sides together and sew. Fold cuff onto wrong side and press. Seam Allowance cuffs turn under at 1 cm and topstitch onto sleeve.

8. Sew on decorative closure.

Технический рисунок:

