Denim Jacket With Trimming - Выкройка #2506



Recommendations on fabric: natural/mixed jeans fabrics; contrasting fabric for decoration.

You will also need: fusible interfacing; 4 buttons.

Seam allowances: all seams 1 cm. Seam allowance for hem of garment – 2.5 cm.

О припусках на швы::
- Если на выкройке двойной контур, припуски на швы уже включены. Они составляют 1 см, если не указано иначе.
- Если у выкройки одинарный контур, припуски на швы не включены, и должны быть добавлены при раскрое.

О требуемой длине ткани:
Внимание! В инструкциях не указано необходимое количество ткани, так как оно зависит от ширины и рисунка ткани, а также Ваших размерных признаков. Прежде всего, распечатайте лекала и разложите их на ширине, соответствующей ширине ткани, которую Вы хотите использовать (обычно от 90 до 150 см), чтобы определить, сколько ткани Вам потребуется. Не забывайте учитывать парные детали и детали со сгибом.

РАСКРОЙ:

Обратите внимание при раскрое:
Обратите внимание на обозначение долевой нити при раскладке деталей. Некоторые детали кроятся со сгибом. Это указано на лекале. Перенесите все отметки и другие особенности дизайна (вытачки и т.п.) с лекала на ткань.
При стачивании деталей, обращайте внимание на надсечки, они должны совпадать.

Main fabric:
1. Center back – cut 2
2. Side back – cut 2
3. Side front – cut 2
4. Upper front – cut 2
5. Center front – cut 2
6. Upper sleeve – cut 2
7. Lower sleeve – cut 2

8. Cuff – cut 2
9. Center front facing – cut 2
10. Lapel – cut 4
11. Stand collar – cut 2
12. Back neck facing – cut 1

Decorative fabric:
1. Front inset – cut 2

Fusible interfacing:
1. Center front facing – cut 2
2. Lapel – cut 2
3. Back neck facing – cut 1

Инструкции:

1. Apply fusible interfacing.

2. Sew side backs to center back, press towards center, serge and topstitch at 0.5 cm from seam. Sew center back seam, press towards left, serge and topstitch at 0.5 cm from seam.

3. Sew upper front to side front, press towards top, serge and topstitch at 0.5 cm from seam. Sew side fronts to front, press towards center, serge and topstitch at 0.5 cm from seam.

4. Sew front inset to garment to front, clipping into seam allowance near corner. Press the seam allowances toward the insert, serge.

5. Sew shoulder and side seams, press seam allowances towards back and serge.

6. Pin lapels together, right sides together and sew the outer edge. Clip seam allowances, turn the lapels right side out, straighten and press. Pin stand collars together right sides together and sew the outer edge. Clip seam allowances, turn stand collar right side out, straighten and press.

7. Pin lapels onto center front and topstitch at neckline edge. Sew the stand collar into neckline.

8. Sew shoulder edges of center front facings and back neckline facing, press the seam apart. Serge the outer edge. Pin center front facing onto main piece, right sides together, pin together and sew center front edge, front neckline, back neckline and lower edge. When stitching make sure to place the front piece on top. Topstitch seam allowance of the central front facing onto the central front facing. Place stitch line at 0,2 cm from seam. Turn center front facing onto wrong side, straighten, press. Baste to the main piece along the shoulder edges.

9. Serge the elbow edges of the sleeve separately. Sew the elbow seam of sleeve from the cap to the mark, clip into seam allowance near the notch. Press the seam allowance on the area from sleeve cap to mark and sew a decorative stitch along the seam at 0.5 cm. Press apart the seam allowances on the area from the mark down to hem and sew decorative stitch along the edges at 0.1 cm. Sew front seam on sleeve, press seam allowances towards lower part and serge. Sew sleeves into armholes matching notches, serge and press.

10. Fold cuffs in half lengthwise right sides together and sew short sides. Start and stop stitching exactly at the marked line of the cuff seam. Turn cuff right side out, straighten and press. Sew outer side of cuff to lower edge of sleeve, press towards cuff. Fold the seam allowance of the inner side onto the wrong side and press and topstitch into seam of.

11. Make buttonholes on right front, sew on buttons onto left front. Make buttonholes and sew on buttons onto cuffs.

Технический рисунок:

