Dress With Decorative Lapels - Выкройка #2512

Recommendations on fabric: natural/mixed fabric suitable for dresses.



You will also need: fusible interfacing; dress zipper.

Seam allowances: all seams 1 cm; seam allowance for hem of dress and hem of sleeve – 3 cm.

О припусках на швы::
- Если на выкройке двойной контур, припуски на швы уже включены. Они составляют 1 см, если не указано иначе.
- Если у выкройки одинарный контур, припуски на швы не включены, и должны быть добавлены при раскрое.

О требуемой длине ткани:
Внимание! В инструкциях не указано необходимое количество ткани, так как оно зависит от ширины и рисунка ткани, а также Ваших размерных признаков. Прежде всего, распечатайте лекала и разложите их на ширине, соответствующей ширине ткани, которую Вы хотите использовать (обычно от 90 до 150 см), чтобы определить, сколько ткани Вам потребуется. Не забывайте учитывать парные детали и детали со сгибом.

РАСКРОЙ:

Обратите внимание при раскрое:
Обратите внимание на обозначение долевой нити при раскладке деталей. Некоторые детали кроятся со сгибом. Это указано на лекале. Перенесите все отметки и другие особенности дизайна (вытачки и т.п.) с лекала на ткань.
При стачивании деталей, обращайте внимание на надсечки, они должны совпадать.

Main fabric:
1. Upper center back - cut 2
2. Upper side back - cut 2
3. Lower back - cut 2
4. Upper center front - cut 1
5. Upper side front - cut 2
6. Lower front – cut 1 on fold
7. Lapel – cut 4

8. Collar — cut 4
9. Sleeve – cut 2

Fusible interfacing:
1. Lapel – cut 2
2. Collar — cut 2

Инструкции:

1. Apply fusible interfacing.

2. Sew princess seams on upper back, press seam allowances towards center, serge.

3. Pin collars together pairwise right sides together and sew the outer edge up to notch. Clip into seam allowance near the notch, turn collar right side out, press. Pin lapels together pairwise right sides together and sew the outer edge up to notch. Clip into seam allowance near the notch, turn lapel right side out, press. Pin collars to lapels and sew along the lapel corner edge, press the seam apart.

4. Sew shoulder seams, press towards the back and serge.

5. Serge the edge of one-piece facing on upper center front, press facing onto wrong side and finish with hidden stitches. Pin center front to lapel and collar, right sides together. Pin these pieces to side front and back, right sides together. Sew lapel and collar to side front and to back neckline, sewing center front to lapel and collar at the same time. Press the seam allowances away from the center and serge.

6. Sew darts on lower backs and on lower front, press bulk towards center. Sew upper front to lower front, sew upper back to lower back, serge and press towards bottom.

7. Serge center back edges separately on each piece. Sew the center back seam from the mark to the bottom edge, press the seam apart. Sew in zipper.

8. Sew side seams, press towards back and serge.

9. Sew sleeve seam, press towards back and serge. Sew sleeves into armholes, serge and press.

10. Serge hem of dress and hem of sleeve, press onto wrong side and finish with hidden stitches.

Технический рисунок:

