Asymmetrical Knit Dress - Выкройка #2580



Recommendations on fabric: natural/mixed knit fabric of small stretchiness in contrasting or similar color.

Seam allowances: all seams 1 cm; seam allowance for hem of dress – 2.0 cm.

О припусках на швы::
- Если на выкройке двойной контур, припуски на швы уже включены. Они составляют 1 см, если не указано иначе.
- Если у выкройки одинарный контур, припуски на швы не включены, и должны быть добавлены при раскрое.

О требуемой длине ткани:
Внимание! В инструкциях не указано необходимое количество ткани, так как оно зависит от ширины и рисунка ткани, а также Ваших размерных признаков. Прежде всего, распечатайте лекала и разложите их на ширине, соответствующей ширине ткани, которую Вы хотите использовать (обычно от 90 до 150 см), чтобы определить, сколько ткани Вам потребуется. Не забывайте учитывать парные детали и детали со сгибом.

РАСКРОЙ:

Обратите внимание при раскрое:
Обратите внимание на обозначение долевой нити при раскладке деталей. Некоторые детали кроятся со сгибом. Это указано на лекале. Перенесите все отметки и другие особенности дизайна (вытачки и т.п.) с лекала на ткань.
При стачивании деталей, обращайте внимание на надсечки, они должны совпадать.

Attention! The pattern pieces are printed as seen from the right side. Turn them over when cutting from the wrong side of fabric!

Main fabric:

1. Upper back - cut 1

2. Upper front - cut 1

3. Front inset - cut 1

4. Sleeve - cut 2

Main fabric 1:

1. Lower left back - cut 1

2. Lower right back - cut 1

3. Lower front - cut 1

4. Collar - cut 1

5. Cuff - cut 2

Инструкции:

1. Sew darts on back and front. Press the bulk of waist darts towards center, press bulk of bust darts towards top.

2. Sew left lower back to right lower back, press the seam allowances towards the left part and serge. Sew upper back to lower back, press towards top and serge.

3. Sew inset to lower front, press seam allowances towards top and serge.

4. Make and baste box pleats on lower front. Sew upper front to lower front, press towards top and serge.

5. Sew shoulder and side seams, press towards the back and serge.

6. Sew collar into a ring, press the seam apart. Fold collar in half lengthwise right side out and press. Sew collar into neckline, slightly stretching it. Serge and press.

7. Sew sleeve seam, press towards the back and serge. Sew sleeves into armholes matching notches and adjusting ease, serge and press.

8. Sew cuff into a ring, press the seam apart. Fold cuff in half lengthwise right side out and press. Sew cuff to lower edge of sleeve, slightly stretching it. Serge and press.

9. Serge bottom edge of garment, press onto wrong side and topstitch.

Технический рисунок:

