Asymmetrical Skirt - Выкройка #2593

Recommendations on fabric: well draping natural/mixed fabrics suitable for skirts.

You will also need: fusible interfacing; 1 button; dress zipper.

Seam allowances: all seams 1 cm. Seam allowance along the lower edges – 1.5 cm.



О припусках на швы::
- Если на выкройке двойной контур, припуски на швы уже включены. Они составляют 1 см, если не указано иначе.
- Если у выкройки одинарный контур, припуски на швы не включены, и должны быть добавлены при раскрое.

О требуемой длине ткани:
Внимание! В инструкциях не указано необходимое количество ткани, так как оно зависит от ширины и рисунка ткани, а также Ваших размерных признаков. Прежде всего, распечатайте лекала и разложите их на ширине, соответствующей ширине ткани, которую Вы хотите использовать (обычно от 90 до 150 см), чтобы определить, сколько ткани Вам потребуется. Не забывайте учитывать парные детали и детали со сгибом.

РАСКРОЙ:

Обратите внимание при раскрое:
Обратите внимание на обозначение долевой нити при раскладке деталей. Некоторые детали кроятся со сгибом. Это указано на лекале. Перенесите все отметки и другие особенности дизайна (вытачки и т.п.) с лекала на ткань.
При стачивании деталей, обращайте внимание на надсечки, они должны совпадать.

Main fabric:
1. Back skirt – cut 1 on fold
2. Front right skirt – cut 1
3. Front left skirt – cut 1
4. Front central skirt – cut 1
5. Belt – cut 1

Fusible interfacing:

1. Belt – cut 1

Инструкции:

1. Apply fusible interfacing.

2. Sew darts on the back skirt, press bulk towards center of pieces.

3. Sew side fronts to front. Serge seams and press towards center.

4. Serge separately left side edges. Sew left side seam from notch for zipper to bottom. Press the seam apart. Sew in zipper. Sew right side seam, press seam allowances towards back skirt and serge.

5. Fold belt in half lengthwise, right sides together and sew the shorter side and the corner. Start stitching exactly at the marked line of seam between belt and skirt. Clip into seam allowances near the notch, belt turn right side out and press. Sew outer edge of belt to upper edge, turn inner edge under and topstitch into seam of.

6. Serge seam allowance along hem, fold inside onto wrong side and topstitch. You may also finish the edge with baby hem, in this case trim away the seam allowance to 0.5 cm.

7. Make buttonhole on belt. Sew on a button.

Технический рисунок:



