Summer Vest - Выкройка #2596

Recommendations on fabric: thick natural/mixed fabric suitable for dresses.



You will also need: fusible interfacing; 2 buttons.

Seam allowances: Seam allowance for hem of garment – 2 cm; other seams – 1 cm.

О припусках на швы::
- Если на выкройке двойной контур, припуски на швы уже включены. Они составляют 1 см, если не указано иначе.
- Если у выкройки одинарный контур, припуски на швы не включены, и должны быть добавлены при раскрое.

О требуемой длине ткани:
Внимание! В инструкциях не указано необходимое количество ткани, так как оно зависит от ширины и рисунка ткани, а также Ваших размерных признаков. Прежде всего, распечатайте лекала и разложите их на ширине, соответствующей ширине ткани, которую Вы хотите использовать (обычно от 90 до 150 см), чтобы определить, сколько ткани Вам потребуется. Не забывайте учитывать парные детали и детали со сгибом.

РАСКРОЙ:

Обратите внимание при раскрое:
Обратите внимание на обозначение долевой нити при раскладке деталей. Некоторые детали кроятся со сгибом. Это указано на лекале. Перенесите все отметки и другие особенности дизайна (вытачки и т.п.) с лекала на ткань.
При стачивании деталей, обращайте внимание на надсечки, они должны совпадать.

Main fabric:
1. Center back - cut 2
2. Side back - cut 2
3. Center front - cut 2
4. Side front - cut 2
5. Stand collar – cut 2
6. Center front facing – cut 2
7. Back neck facing - cut 1

Lining:
1. Center back - cut 2
2. Side back - cut 2
3. Front lining - cut 2

Attention! The central backs from lining are cut using the pattern pieces for the main fabric except for the width of the back neckline facing.

Fusible interfacing:
1. Center front - cut 2
2. Stand collar – cut 1
3. Center front facing – cut 2
4. Back neck facing - cut 1

Инструкции:

1. Apply fusible interfacing.

2. Sew side backs to center back, press towards center. Sew the center back seam, press the seam apart.

3. Sew side fronts to front, press towards center.

4. Sew side and shoulder seams, press the seam apart.

5. Pin stand collars together, right sides together and sew collar ends and the outer edge of collar. Trim away corners, snip into seam allowance near the mark. Turn stand collar right side out, straighten and press. Sew the stand collar into neckline, snipping into seam allowances of the front in the corners.

6. Sew side seams of center front facings and back neckline facings, press the seam apart.

7. Pin together center front facings and front right sides together and sew the center front edge, the neckline and the lower corner, stopping at 1.5 cm from the edge of the center front facing. Trim away corners, clip into curves. Fold the center front facings onto right side, straighten seams, press.

8. Sew darts and seams on lining, leaving an opening in left side seam. Sew lining to inner edges of the center front facings and to the facing. Sew lining to armhole in two steps: first sew the front armhole, then sew the back armhole.

9. Press lower edge of garment onto wrong side. Sew lining to lower edge of garment. Turn the vest right side out through the opening. Sew the opening closed. Sew a decorative/fixing stitch line along the lower edge.

10. Make buttonholes on right front, sew on buttons onto left front.

Технический рисунок:



