Blouse With Decorative Front - Выкройка #2788

Recommendations on fabric: soft natural/mixed knit fabric of medium stretchiness.

You will also need: knit fusible interfacing.

Seam allowances: all seams - 1.0 cm; seam allowance for hem of garment and hem of sleeve – 1.5 cm. Seam allowance along the outer edge of the decorative front piece – 1.5 cm.



О припусках на швы::
- Если на выкройке двойной контур, припуски на швы уже включены. Они составляют 1 см, если не указано иначе.
- Если у выкройки одинарный контур, припуски на швы не включены, и должны быть добавлены при раскрое.

О требуемой длине ткани:
Внимание! В инструкциях не указано необходимое количество ткани, так как оно зависит от ширины и рисунка ткани, а также Ваших размерных признаков. Прежде всего, распечатайте лекала и разложите их на ширине, соответствующей ширине ткани, которую Вы хотите использовать (обычно от 90 до 150 см), чтобы определить, сколько ткани Вам потребуется. Не забывайте учитывать парные детали и детали со сгибом.

РАСКРОЙ:

Обратите внимание при раскрое:
Обратите внимание на обозначение долевой нити при раскладке деталей. Некоторые детали кроятся со сгибом. Это указано на лекале. Перенесите все отметки и другие особенности дизайна (вытачки и т.п.) с лекала на ткань.
При стачивании деталей, обращайте внимание на надсечки, они должны совпадать.

Attention! Pattern blocks have markings and texts from the right side. Take this into account when cutting the fabric-some of the pattern blocks need to be laid onto fabric with their wrong side on top!

Main fabric:
1. Back – cut 1 on fold
2. Front – cut 1 on fold
3. Overlay front – cut 1
4. Sleeve – cut 2

5. Back neck facing – cut 2

Fusible interfacing:
1. Back neck facing – cut 1

Инструкции:

1. Apply fusible interfacing.

2. Serge the outer and the lower edges of the decorative front piece, press onto wrong side and topstitch.

3. Sew a gathering stitch along the left shoulder edge of the decorative front piece and gather fullness. Pin the decorative front piece with right side down onto the wrong side of the front and sew the upper edge of the one-piece stand collar. Clip seam allowances, fold the decorative front onto the right side of the front and baste together along raw edges. Treat as one piece in the future.

4. Pin back neckline facing to back right sides together and sew the upper edge of the one-piece stand collar, start and stop stitching exactly at the line of the shoulder seam.

5. Sew shoulder seams, inserting the front in between the facing and the back. Turn the piece right side out, straighten, press.

6. Sew side seams, press towards the back and serge.

7. Sew sleeve seam, press towards the back and serge. Sew sleeves into armholes, matching notches, serge and press.

8. Seam allowance for hem of garment and hem of sleeve serge, fold inside onto wrong side and topstitch.

Технический рисунок:

