Waistcoat With Longer Front - Выкройка #2823



Recommendations on fabric: natural/mixed suiting fabrics.

You will also need: fusible interfacing; lining; 1 inner button.

Seam allowances: all seams 1 cm. Seam allowance for hem of garment – 2.5 cm.

О припусках на швы::
- Если на выкройке двойной контур, припуски на швы уже включены. Они составляют 1 см, если не указано иначе.
- Если у выкройки одинарный контур, припуски на швы не включены, и должны быть добавлены при раскрое.

О требуемой длине ткани:
Внимание! В инструкциях не указано необходимое количество ткани, так как оно зависит от ширины и рисунка ткани, а также Ваших размерных признаков. Прежде всего, распечатайте лекала и разложите их на ширине, соответствующей ширине ткани, которую Вы хотите использовать (обычно от 90 до 150 см), чтобы определить, сколько ткани Вам потребуется. Не забывайте учитывать парные детали и детали со сгибом.

РАСКРОЙ:

Обратите внимание при раскрое:
Обратите внимание на обозначение долевой нити при раскладке деталей. Некоторые детали кроятся со сгибом. Это указано на лекале. Перенесите все отметки и другие особенности дизайна (вытачки и т.п.) с лекала на ткань.
При стачивании деталей, обращайте внимание на надсечки, они должны совпадать.

Main fabric:
1. Center back – cut 2
2. Side back – cut 2
3. Center front – cut 2
4. Side front – cut 2
5. Center front facing - cut 2
6. Back neck facing – cut 1

Attention: lining for front and back is cut using the pattern blocks for main fabric except for the width of the

center front facing and back neckline facing.

Lining:
1. Center back – cut 2
2. Side back – cut 2
3. Center front – cut 2
4. Side front – cut 2

Fusible interfacing:
1. Center front – cut 2
2. Center front facing – cut 2
3. Back neck facing – cut 1

Инструкции:

1. Apply fusible interfacing.

2. Sew the center back seam, press the seam apart. Sew side backs to center back. Press towards center.

3. Cut two straps of fabric on bias for ties, they should be 2.5 cm wide and 50 cm long. Fold tape in half lengthwise right sides together and stitch at 0.3 cm from fold. Cut away seam allowances close to seam, turn tape right side out and straighten the rolled piece. Cut in two.

4. Sew side front to center front, inserting the tie band into the right princess seam. Press towards center.

5. Sew shoulder and side seams. Press the seam apart.

6. Sew side seams of back neckline facing and central front facings, press seam apart.

7. Pin center front facings onto the main piece right sides together, pin together and sew center front facings and neckline. Insert the second tie into the left center front seam. Clip seam allowances, fold the center front facings and the facing onto the wrong side and press.

8. Fold inside the lower edge of the vest and press.

9. Sew seams on lining, leaving an opening in left side seam. Sew lining to the central front facings and to facing. Sew lining to armhole in two steps: first sew the front armhole, then sew the back armhole. Clip seam allowances, turn right side out and press. Sew lining to lower edge of vest.

10. Turn the vest right side out through the technical opening. Sew the opening closed.

11. Make the inner button hole. Sew on inner button.

Технический рисунок:



