Dress With Transparent Yoke - Sewing Pattern #4402

Recommendations on fabric: natural/mixed knit fabric of medium/high stretchiness; transparent knit fabric of similar color.



Seam allowances: seam allowance for hem of garment – 2.0 cm, other seam allowances – 0.7 cm.

Note on seam allowances:
- If the pattern has double contour the seam allowances are included. They are 1 cm unless specified otherwise.
- If the pattern has single contour, the seam allowances are NOT included and need to be added when laying out the pattern.

Note on length of fabric:
Attention! The amount of fabric needed for your pattern is not included. It will depend on the selected pattern size, the width, and design of the fabric you plan to use. First, print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm). Measure how much fabric you will need. Don't forget to account for pieces that need to be cut multiple times and pieces that are cut on the fold.

Note on working with stretchy fabric:
Knitted fabric pieces are sewn together with special elastic or narrow zig-zag stitch. Seam allowance on hems can be stitched with twin needles to save stretchiness. Pieces can also be sewn together with a serger. When serging, cut seam allowances to 0.6 – 0.8 cm.

CUTTING:

Note on cutting:
On the pattern pieces, “beam” means straight of grain. Lay out your pieces accordingly. Some pieces will be cut on the fold. This is noted on the pattern piece. Mark all notches and other design features such as pleats etc. from the pattern onto your fabric.
When sewing the garment, pay attention to notches, they must match up.

Main fabric:
1. Center back - cut 2
2. Side back - cut 2
3. Side front – cut 2
4. Center front – cut 1
5. Front neck facing — cut 2

6. Back neck facing — cut 2
7. Cuff – cut 2

Transparent fabric:
1. Front yoke - cut 1
2. Sleeve - cut 2

INSTRUCTIONS:

1. Sew side backs to center back. Sew side fronts to front. Serge seams and press towards center.

2. Sew center back seam. Press towards left and serge.

3. On upper edge of front yoke sew a gathering stitch and gather fullness. Sew front yoke to sleeve. Serge and press.

4. Pin facing on garment, right sides together. Sew the front neckline, turn right side out, press. Sew back facings to front facings, press in half. Sew the back neckline.

5. Sew front yoke to front, serge and press. Sew sleeve to back. Serge and press.

6. Sew side seams and sleeve seams.

7. Sew cuff into a ring. Fold cuff in half lengthwise and sew cuff to lower edge of sleeve. Serge the seam allowances.

8. Serge bottom edge of dress, press onto wrong side and topstitch.

TECHNICAL DRAWING:

