Blouse With Slanted Dart - Выкройка #4767



Recommendations on fabric: natural/mixed fabrics suitable for blouses.

You will also need: fusible interfacing.

Seam allowances: seam allowance for hem of garment and hem of sleeve – 2 cm, other seams 1 cm.

О припусках на швы::
- Если на выкройке двойной контур, припуски на швы уже включены. Они составляют 1 см, если не указано иначе.
- Если у выкройки одинарный контур, припуски на швы не включены, и должны быть добавлены при раскрое.

О требуемой длине ткани:
Внимание! В инструкциях не указано необходимое количество ткани, так как оно зависит от ширины и рисунка ткани, а также Ваших размерных признаков. Прежде всего, распечатайте лекала и разложите их на ширине, соответствующей ширине ткани, которую Вы хотите использовать (обычно от 90 до 150 см), чтобы определить, сколько ткани Вам потребуется. Не забывайте учитывать парные детали и детали со сгибом.

РАСКРОЙ:

Обратите внимание при раскрое:
Обратите внимание на обозначение долевой нити при раскладке деталей. Некоторые детали кроятся со сгибом. Это указано на лекале. Перенесите все отметки и другие особенности дизайна (вытачки и т.п.) с лекала на ткань.
При стачивании деталей, обращайте внимание на надсечки, они должны совпадать.

Main fabric:
1. Front – cut 1 on fold
2. Back – cut 1 on fold
3. Cuff – cut 2
4. Back neck facing – cut 1
5. Front neck facing – cut 1

Fusible interfacing:
1. Back neck facing – cut 1
2. Front neck facing – cut 1

Инструкции:

1. Apply interfacing to facings.

2. Sew darts on front, press the inner part towards center. Make and sew box pleat from neckline edge to marking..

3. Sew shoulder seams, press towards the back and serge.

4. Sew a gathering stitch along the upper edge of the cuff and gather fullness. Sew the cuff to the sleeve, press seam allowances towards sleeve and serge.

5. Sew side seams processing the sleeve seam at the same time, press towards the back and serge.

6. Sew shoulder seams of facings, press the seam apart. Serge the outer edge. Pin facings to garment right sides together and sew the neckline. Clip into curves, turn the facings onto the wrong side and press. Baste facings to shoulder seams.

7. Serge lower edge of garment and lower edge of sleeve, press onto wrong side and topstitch.

Технический рисунок:

