Blouse With Pleat - Выкройка #4770

Recommendations on fabric: natural/mixed fabrics suitable for blouses, companion fabric.



You will also need: fusible interfacing, 3 buttons.

Seam allowances: seam allowance along hem of garment and hem of sleeve – 2 cm, other seams 1 cm.

О припусках на швы::
- Если на выкройке двойной контур, припуски на швы уже включены. Они составляют 1 см, если не указано иначе.
- Если у выкройки одинарный контур, припуски на швы не включены, и должны быть добавлены при раскрое.

О требуемой длине ткани:
Внимание! В инструкциях не указано необходимое количество ткани, так как оно зависит от ширины и рисунка ткани, а также Ваших размерных признаков. Прежде всего, распечатайте лекала и разложите их на ширине, соответствующей ширине ткани, которую Вы хотите использовать (обычно от 90 до 150 см), чтобы определить, сколько ткани Вам потребуется. Не забывайте учитывать парные детали и детали со сгибом.

РАСКРОЙ:

Обратите внимание при раскрое:
Обратите внимание на обозначение долевой нити при раскладке деталей. Некоторые детали кроятся со сгибом. Это указано на лекале. Перенесите все отметки и другие особенности дизайна (вытачки и т.п.) с лекала на ткань.
При стачивании деталей, обращайте внимание на надсечки, они должны совпадать.

Main fabric:

1. Front – cut 1 on fold
2. Back yoke – cut 1
3. Sleeve – cut 2
4. Back facing – cut 1
5. Front facing - cut 1

Main fabric 1:

1. Back – cut 1 on fold
2. Cuff – cut 2

Fusible interfacing:

1. Back facing – cut 1
2. Front facing - cut 1

Инструкции:

1. Apply fusible interfacing to facings.

2. Sew yoke to back, press towards top and serge.

3. Make, press and slip stitch darts on front. Make and baste a box pleat on front.

4. Sew shoulder and side seams, press towards the back and serge.

5. Sew shoulder seams of facings, press the seam apart. Serge the outer edge. Pin facing onto neckline right sides together and sew the neckline. Clip seam allowances, turn facing onto wrong side and press. Topstitch seam allowances onto facing at 0.2 cm from seam. Slip stitch facing to shoulder seams.

6. Sew the cuff to the sleeve, press towards top and serge. Sew sleeve seam, press towards back and serge. Sew sleeves into armholes matching notches and adjusting ease, serge and press.

7. Serge the hem of the garment and the hem of sleeve. press onto wrong side and topstitch.

8. Sew on decorative buttons on the pleat.

Технический рисунок:

