

Jacket With Belt And Decorative Closure - Sewing Pattern #4773

Recommendations on fabric: natural/mixed suiting fabrics.

You will also need: fusible interfacing; lining; shoulder pads; 4 buttons; decorative closing.

Seam allowances: all seams 1 cm. Seam allowance along hem of jacket and hem of sleeve - 3.0 cm.

Note on seam allowances:

- If the pattern has double contour the seam allowances are included. They are 1 cm unless specified otherwise.
- If the pattern has single contour, the seam allowances are NOT included and need to be added when laying out the pattern.

Note on length of fabric:

Attention! The amount of fabric needed for your pattern is not included. It will depend on the selected pattern size, the width, and design of the fabric you plan to use. First, print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm). Measure how much fabric you will need. Don't forget to account for pieces that need to be cut multiple times and pieces that are cut on the fold.



CUTTING:

Note on cutting:

On the pattern pieces, "beam" means straight of grain. Lay out your pieces accordingly. Some pieces will be cut on the fold. This is noted on the pattern piece. Mark all notches and other design features such as pleats etc. from the pattern onto your fabric.

When sewing the garment, pay attention to notches, they must match up.

Main fabric:

1. Center back - cut 2
2. Side back - cut 2
3. Side front - cut 2
4. Center front - cut 2
5. Center front facing - cut 2
6. Back neck facing - cut 2

7. Front neck facing - cut 4
8. Upper sleeve - cut 2
9. Lower sleeve - cut 2
10. Back belt - cut 1
11. Front belt - cut 2

Lining:

1. Center back - cut 2
2. Side back - cut 2
3. Side front - cut 2
4. Center front - cut 2
5. Upper sleeve - cut 2
6. Lower sleeve - cut 2

Fusible interfacing:

1. Center front facing - cut 2
2. Back neck facing - cut 1
3. Front neck facing - cut 2
4. Front belt - cut 2
5. Back belt - cut 1

INSTRUCTIONS:

1. Apply fusible interfacing.
2. Serge separately, sew and press apart princess seams on the back (sew side backs to center backs). Sew and press apart center back seam.
3. Sew darts on center front according to markings. Sew and press apart princess seams on front (serge separately and sew center fronts to side fronts).
4. Sew side and shoulder seams, press seam apart.
5. Sew shoulder seams of outer neckline facings, press seam apart.

Sew shoulder seams on inner facings горловины, press seam apart. Pin together facings right sides together and sew upper and side edges. Clip into curves, trim away corners. Turn facing right side out, press. Sew facing to Shell.

6. Sew side edges of belts, press seam apart. Press longer edges onto wrong side. Pin belt onto jacket and topstitch at 0.1 cm from the folded edge.

7. Sew the elbow seam of the sleeve and press it apart, adjusting ease on upper part of sleeve and matching notches. Press hem of sleeve. Fold away seam allowance on hem, sew and press apart front sleeve seam.
8. Sew sleeves into armholes matching notches, adjusting ease along upper side of sleeve cap. Sew shoulder pads.
9. Sew seams on lining, sew in sleeves, leaving an opening for turning in left elbow seam. Sew center front facings to lining.
10. Pin center front facing and lining onto Shell front, right sides together, pin together and sew around center front and neckline, placing neckline facing between self fabric and lining. When stitching make sure to place the front piece on top. Topstitch seam allowance on buttonstand onto buttonstand. Place stitch line at 0,2 cm from seam.
11. Sew lining to hem of jacket and hem of sleeve. Turn jacket right side out. Sew the opening closed.
12. On right front make buttonholes, sew on buttons on left front. Sew on decorative closure.

TECHNICAL DRAWING:

