

Tunic - Sewing Pattern #4778

Recommendations on fabric: natural/mixed knit fabric of small stretchiness.

You will also need: knit fusible interfacing; 3 buttons.

Seam allowances: seam allowance for hem of garment and hem of sleeve – 1.2 cm; seam allowance along neckline of upper fronts – 1.2 cm; seam allowance along center seam of upper left front – 1.2 cm; other seams – 0.7 cm.

Note on seam allowances:

- If the pattern has double contour the seam allowances are included. They are 1 cm unless specified otherwise.
- If the pattern has single contour, the seam allowances are NOT included and need to be added when laying out the pattern.

Note on length of fabric:

Attention! The amount of fabric needed for your pattern is not included. It will depend on the selected pattern size, the width, and design of the fabric you plan to use. First, print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm). Measure how much fabric you will need. Don't forget to account for pieces that need to be cut multiple times and pieces that are cut on the fold.



CUTTING:

Note on cutting:

On the pattern pieces, "beam" means straight of grain. Lay out your pieces accordingly. Some pieces will be cut on the fold. This is noted on the pattern piece. Mark all notches and other design features such as pleats etc. from the pattern onto your fabric.

When sewing the garment, pay attention to notches, they must match up.

Knit fabric:

1. Upper left back – cut 1
2. Upper right back – cut 1
3. Lower back – cut 1
4. Upper left front – cut 1
5. Upper right front – cut 1
6. Lower front – cut 1

- 7. Stand collar – cut 2
- 8. Sleeve – cut 2

Fusible interfacing:

- 1. Stand collar – cut 1

INSTRUCTIONS:

1. Apply fusible interfacing to stand collar.
2. Sew center seam on upper back, press towards left and serge. Sew lower back to upper back, press towards top and serge. Sew outer stand collar into neckline, press seam allowances towards stand collar.
3. Sew bust dart on upper left front, trim bulk with serger. Make and topstitch pleats on upper right front according to markings (fold bulk of pleats towards side seam).
4. Serge neckline edge of upper left front, press onto wrong side and topstitch. Sew upper left front to right front. Serge seam allowances, at the same time serging the neckline edge of right front. Press seam allowance along neckline of right front onto wrong side and topstitch.
5. Sew upper front to lower front, serge and press towards bottom.
6. Serge lower seam allowance of inner stand collar onto wrong side. Pin inner stand collar to outer stand collar right sides together and sew along upper edge exactly up to the marked line of shoulder seam. Clip seam allowances.
7. Sew shoulder edges, placing them between inner and outer stand collars. Press seams towards back, serge. Turn pieces right side out. Topstitch the inner collar in the seam of the outer collar.
8. Hem of sleeve serge, press onto wrong side and topstitch. Sew sleeve into open armhole, serge and press.
9. Sew sleeve seams and continue sewing side seams, press towards the back and serge.
10. Serge the lower edge of garment, press onto wrong side and topstitch.
11. Sew decorative buttons onto right upper front.

TECHNICAL DRAWING:

