

Outdoor Jacket Combined With Knit Details - Sewing Pattern #4814

Recommendations on fabric: natural/mixed fabrics suitable for outdoor jackets, knit fabric of small stretchiness.

You will also need: separating zipper, lining.

Seam allowances: Seam allowance for hem of garment and hem of sleeve — 3 cm, along lower edge of pockets — 0 cm, all other seams 1 cm.

Note on seam allowances:

- If the pattern has double contour the seam allowances are included. They are 1 cm unless specified otherwise.
- If the pattern has single contour, the seam allowances are NOT included and need to be added when laying out the pattern.

Note on length of fabric:

Attention! The amount of fabric needed for your pattern is not included. It will depend on the selected pattern size, the width, and design of the fabric you plan to use. First, print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm). Measure how much fabric you will need. Don't forget to account for pieces that need to be cut multiple times and pieces that are cut on the fold.



CUTTING:

Note on cutting:

On the pattern pieces, "beam" means straight of grain. Lay out your pieces accordingly. Some pieces will be cut on the fold. This is noted on the pattern piece. Mark all notches and other design features such as pleats etc. from the pattern onto your fabric.

When sewing the garment, pay attention to notches, they must match up.

Main fabric (knit fabric):

1. Center back - cut 2
2. Side back - cut 2
3. Side front - cut 2
4. Sleeve - cut 2
5. Hood — cut 2

6. Center hood - cut 1
7. Pocket bag large — cut 2
8. Pocket bag small - cut 2

Main fabric 1(waterproof):

1. Center front - cut 2
2. Center front facing — cut 2
3. Back yoke - cut 1
4. Front yoke - cut 2
5. Hood facing - cut 1
6. Back neck facing - cut 1

Lining:

1. Center back - cut 2
2. Side back - cut 2
3. Side front - cut 2
4. Sleeve - cut 2
5. Hood — cut 2
6. Center hood - cut 1
8. Center front - cut 2
9. Back yoke - cut 1
10. Front yoke - cut 2

INSTRUCTIONS:

1. Pin smaller pocket bag onto right side of center part and sew pocket opening. Trim away corners. Fold pocket bag onto wrong side and press. Pin center part onto larger lining and sew seam allowances of pocket bags. Sew side front to front. Serge seams and press towards center. Sew yoke to front. Serge and press towards top.
2. Sew side backs to center back. Press towards center. Sew yoke to back. Press seam allowance towards top.
3. Sew shoulder seams. Press seams towards back. Sew sleeve into armhole. Sew side seam, and continue sewing the sleeve seam.
4. Sew center part to hood. Pin facing onto hood and baste together along outer edge. Fold inside seam allowance along inner edge, onto wrong side and topstitch at hood from the right side. Sew hood into neckline.
5. Sew shoulder seam of back neckline facing and center front facing. Sew hood lining into neckline of facings.
6. Pin self to center front facings right sides together, insert zipper between the pieces and sew center front edge and outer edge of hood. Fold center front facings onto wrong side. Baste together seam allowances of the hood seam.

7. Sew lining, leaving an opening in left side seam. Sew in sleeves. Sew lining to facing, center front facings, to hem of jacket and pykavam. Turn right side out through the opening. Sew the opening closed.

TECHNICAL DRAWING:

