Dress With Gathers - Выкройка #4858

Recommendations on fabric: natural/mixed fabric suitable for dresses.

You will also need: fusible interfacing.

Seam allowances: all seams 1 cm. Seam allowance along hem of dress – 3.0 cm.



О припусках на швы::
- Если на выкройке двойной контур, припуски на швы уже включены. Они составляют 1 см, если не указано иначе.
- Если у выкройки одинарный контур, припуски на швы не включены, и должны быть добавлены при раскрое.

О требуемой длине ткани:
Внимание! В инструкциях не указано необходимое количество ткани, так как оно зависит от ширины и рисунка ткани, а также Ваших размерных признаков. Прежде всего, распечатайте лекала и разложите их на ширине, соответствующей ширине ткани, которую Вы хотите использовать (обычно от 90 до 150 см), чтобы определить, сколько ткани Вам потребуется. Не забывайте учитывать парные детали и детали со сгибом.

РАСКРОЙ:

Обратите внимание при раскрое:
Обратите внимание на обозначение долевой нити при раскладке деталей. Некоторые детали кроятся со сгибом. Это указано на лекале. Перенесите все отметки и другие особенности дизайна (вытачки и т.п.) с лекала на ткань.
При стачивании деталей, обращайте внимание на надсечки, они должны совпадать.

Main fabric:
1. Upper back – cut 1 on fold
2. Upper front - cut 1 on fold
3. Lower back – cut 1 on fold
4. Lower front - cut 1 on fold
5. Collar - cut 1
6. Cuff - cut 2
7. Larger belt – cut 1

8. Smaller belt – cut 2
9. Pocket bag – cut 4

Fusible interfacing:
1. Larger belt – cut 1
2. Smaller belt – cut 2

Инструкции:

1. Sew shoulder seams of upper parts. Serge seams and press towards back. Sew side seams and sleeve seams continuously. Serge seams and press towards back.

2. Sew pocket bag to lower front and to lower back. Start and stop stitching exactly at the marked line of the pocket opening. Clip seam allowances near notches. Sew edges of pocket lining. Sew side edges of lower parts in two steps: from top to beginning of pocket, and from pocket to hem. Serge seams and press towards back. Sew a gathering stitch along upper edges of lower part and gather fullness.

3. Sew upper part of dress to lower part of dress. Serge and press towards top.

4. Sew collar into a ring. Press the seam allowances apart. Fold collar in half lengthwise. Sew the outer collar into neckline. Fold under the seam allowance of the inner side inside and stitch in the ditch.

5. Sew cuff into a ring. Press the seam allowances apart. Fold cuff in half lengthwise. Sew outer side of cuff to sleeve. Fold under the seam allowance of the inner side inside and topstitch into seam of.

6. Fold smaller belt in half lengthwise, right sides together, and sew along longer and one short edges. Trim away corners, turn right side out. Fold larger belt in half lengthwise right sides together. Inner smaller belts into the belt, align side edges and sew the belt, leaving an opening for turning. Turn belt right side out and press. Sew the opening closed.

7. Serge the lower edge of dress, press onto wrong side and topstitch.

Технический рисунок:

