4876 - Sewing Pattern #4876

Recommandations sur le tissu: épais tissu naturel/mixte pour chemisiers.

Marges de couture: marge de couture pour l'ourlet du vêtement et l'ourlet de la manche – 2.0 cm, autres coutures - 1.0 cm.



Note on seam allowances:
- If the pattern has double contour the seam allowances are included. They are 1 cm unless specified otherwise.
- If the pattern has single contour, the seam allowances are NOT included and need to be added when laying out the pattern.

Note on length of fabric:
Attention! The amount of fabric needed for your pattern is not included. It will depend on the selected pattern size, the width, and design of the fabric you plan to use. First, print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm). Measure how much fabric you will need. Don't forget to account for pieces that need to be cut multiple times and pieces that are cut on the fold.

CUTTING:

Note on cutting:
On the pattern pieces, “beam” means straight of grain. Lay out your pieces accordingly. Some pieces will be cut on the fold. This is noted on the pattern piece. Mark all notches and other design features such as pleats etc. from the pattern onto your fabric.
When sewing the garment, pay attention to notches, they must match up.

Tissu principal:
1. Devant – 1 pièce au pli
2. Dos – 1 pièce au pli
3. Col – 1 pièce
4. Manche – 2 pièces

INSTRUCTIONS:

1. Coudre les pinces devant (). Repassez la partie intérieure vers le haut.

2. Coudre des pinces sur le dos. Repassez la partie intérieure vers le centre.

3. Coudre les coutures des épaules, repassez les coutures vers l'arrière et surjeter.

4. Col épingler ensemble en deux dans le sens de la longueur à l'endroit. et faire des fronces. le long du bord inférieur. Coudre le col dans l'encolure, couper les coins, repasser les surplus de couture vers la pièce principale et surjeter. à 0.5 cm.

5. Coudre les manches dans les emmanchures, correspondant à encoches, surjeter et repasser. Coudre les manches et continuer à coudre les côtés, surjeter et repasser.

6. Surjeter le bord inférieur du vêtement et le bord inférieur de la manche, repasser sur l'envers et surpiquer.

TECHNICAL DRAWING:

