Blouson - Sewing Pattern #4878

Recommendations on fabric: natural/mixed fabrics suitable for blouses.

Seam allowances: all seams 1 cm; seam allowance for hem of garment and hem of sleeve - 1.2 cm.



Note on seam allowances:
- If the pattern has double contour the seam allowances are included. They are 1 cm unless specified otherwise.
- If the pattern has single contour, the seam allowances are NOT included and need to be added when laying out the pattern.

Note on length of fabric:
Attention! The amount of fabric needed for your pattern is not included. It will depend on the selected pattern size, the width, and design of the fabric you plan to use. First, print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm). Measure how much fabric you will need. Don't forget to account for pieces that need to be cut multiple times and pieces that are cut on the fold.

CUTTING:

Note on cutting:
On the pattern pieces, “beam” means straight of grain. Lay out your pieces accordingly. Some pieces will be cut on the fold. This is noted on the pattern piece. Mark all notches and other design features such as pleats etc. from the pattern onto your fabric.
When sewing the garment, pay attention to notches, they must match up.

Main fabric:
1. Center back - cut 1 on fold
2. Side back – cut 2
3. Side front – cut 2
4. Center front — cut 1 on fold
5. Sleeve – cut 2
6. Pocket – cut 2

INSTRUCTIONS:

1. Coudre des pinces sur le devant, repassez la partie intérieure vers le haut.
et repasser. . Traiter comme une seule pièce à l'avenir.

2. Coudre les dos latéraux au dos central. Coudre les devants latéraux au devant central. Surjeter les coutures et repasser vers le centre.

3. Coudre les manches au dos, repassez les coutures vers l'arrière et surjeter. Coudre les manches sur le devant, repasser les surplus de couture vers l'avant et surjeter.

4. Coudre les coutures latérales en même temps avec la couture de la manche, surjeter et repasser.

5. Coupez ou utilisez du ruban de biais prêt à l'emploi, sa largeur doit être égale à 4 cm et la longueur doit être égale à la longueur de l'encolure + 5 cm. Plier le biais en deux dans le sens de la longueur à l'endroit et repasser. Épinglez le biais sur l'encolure du côté droit et coudre. Faire de petites coupes dans les marges de couture. Pliez le ruban de biais sur l'envers et surpiquer sur la pièce principale le long de la couture. Repasser la couture.

6. Surjetez la marge de couture pour l'ourlet du vêtement et l'ourlet de la manche, repasser sur l'envers et surpiquer.

TECHNICAL DRAWING:

