

## Two Color Knit Blouse - Sewing Pattern #4893

Recommendations on fabric: natural/mixed knit fabric of medium stretchiness in matching colours.

Seam allowances: all seams 1 cm. Seam allowance for hem of garment – 2 cm. Seam allowance along neckline and hem – 0 cm.

### Note on seam allowances:

- If the pattern has double contour the seam allowances are included. They are 1 cm unless specified otherwise.
- If the pattern has single contour, the seam allowances are NOT included and need to be added when laying out the pattern.

### Note on length of fabric:

Attention! The amount of fabric needed for your pattern is not included. It will depend on the selected pattern size, the width, and design of the fabric you plan to use. First, print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm). Measure how much fabric you will need. Don't forget to account for pieces that need to be cut multiple times and pieces that are cut on the fold.



## CUTTING:

### Note on cutting:

On the pattern pieces, "beam" means straight of grain. Lay out your pieces accordingly. Some pieces will be cut on the fold. This is noted on the pattern piece. Mark all notches and other design features such as pleats etc. from the pattern onto your fabric.

When sewing the garment, pay attention to notches, they must match up.

Main fabric:

1. Lower back – cut 1 on fold
2. Lower front – cut 1 on fold

Main fabric 1:

1. Upper back – cut 1 on fold
2. Upper front – cut 1 on fold

## INSTRUCTIONS:

1. Sew upper front to lower front. Serge the seam and press towards top.
2. Sew upper back to lower back. Serge the seam and press towards top.
3. Sew right shoulder seam. Serge and press towards back.
4. Cut a strap 4 cm wide from Fabric 1, at 45 degrees to grain. Fold bias tape in half lengthwise and press. Lay the piece apart, fold longer edges towards center and press one more time. Finish the neckline with bias tape. Sew left shoulder seam. Serge and press towards back.
5. Sew side seams sewing the sleeve edges at the same time, press towards the back and serge. Finish the edges of sleeves in the same way as the neckline.
6. Serge lower edge of garment, press onto wrong side and topstitch.

## TECHNICAL DRAWING:

