
# Denim Dress With Flounces - Sewing Pattern #4921



Recommendations on fabric: natural/mixed denim fabric.

You will also need: dress zipper.

Seam allowances: Seam allowance for hem of garment – 3.0 cm, other seams – 1 cm.

**Note on seam allowances:**
*- If the pattern has double contour the seam allowances are included. They are 1 cm unless specified otherwise.*
*- If the pattern has single contour, the seam allowances are NOT included and need to be added when laying out the pattern.*

**Note on length of fabric:**
*Attention! The amount of fabric needed for your pattern is not included. It will depend on the selected pattern size, the width, and design of the fabric you plan to use. First, print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm). Measure how much fabric you will need. Don't forget to account for pieces that need to be cut multiple times and pieces that are cut on the fold.*

## CUTTING:

**Note on cutting:**
*On the pattern pieces, “beam” means straight of grain. Lay out your pieces accordingly. Some pieces will be cut on the fold. This is noted on the pattern piece. Mark all notches and other design features such as pleats etc. from the pattern onto your fabric.*
*When sewing the garment, pay attention to notches, they must match up.*

Main fabric:
1. Center back - cut 2
2. Side back - cut 2
3. Side front - cut 2
4. Center front - cut 1
5. Flounce – cut 2

## INSTRUCTIONS:

1. Serge center back edges separately. Sew center back seam from notch for zipper to bottom. Press apart center seam, pressing the slit at the same time. Sew in zipper.

2. Sew shoulder seam on center front/center back, and sew separately shoulder seam on side front/side back, press towards the back and serge.

3. Serge outer edge of flounce, press onto wrong side and topstitch.

4. Pin center front to side front, inserting the flounce in between. Sew. Press to середине, serge. Sew a decorative stitch along the seam at 0.5 cm.

5. Cut (or take ready) bias tape, its width should equal 4 cm and length should equal the length of neckline + 5 cm. Fold bias tape in half lengthwise right side out and press. Pin bias tape to neckline from the right side and sew. Clip into seam allowances. Fold bias tape onto wrong side and topstitch onto main piece along the fold. Press seam.

6. Cut (or take ready) bias tape, its width should equal 4 cm and length should equal the length of armhole + 5 cm. Fold bias tape in half lengthwise right side out and press. Pin bias tape to armhole edge from the right side and sew. Clip into seam allowances. Fold bias tape onto wrong side and topstitch onto main piece along the fold. Press seam.

7. Press lower edge of garment onto wrong side at 1 cm, then again at 2 cm and topstitch.

## TECHNICAL DRAWING:

