Dress With Ties - Sewing Pattern #4936

Recommendations on fabric: natural/mixed fabric suitable for dresses.

You will also need: fusible interfacing, 7 buttons.

Seam allowances: all seams 1 cm. Seam allowance for hem of garment and hem of sleeve – 2 cm.



Note on seam allowances:
- If the pattern has double contour the seam allowances are included. They are 1 cm unless specified otherwise.
- If the pattern has single contour, the seam allowances are NOT included and need to be added when laying out the pattern.

Note on length of fabric:
Attention! The amount of fabric needed for your pattern is not included. It will depend on the selected pattern size, the width, and design of the fabric you plan to use. First, print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm). Measure how much fabric you will need. Don't forget to account for pieces that need to be cut multiple times and pieces that are cut on the fold.

CUTTING:

Note on cutting:
On the pattern pieces, “beam” means straight of grain. Lay out your pieces accordingly. Some pieces will be cut on the fold. This is noted on the pattern piece. Mark all notches and other design features such as pleats etc. from the pattern onto your fabric.
When sewing the garment, pay attention to notches, they must match up.

Из основной ткани:
1. Верхняя часть спинки – 2 детали со сгибом
2. Центральная часть спинки – 1 деталь со сгибом
3. Боковая часть спинки – 2 детали
4. Верхняя часть полочки – 4 детали
5. Центральная часть полочки – 2 детали
6. Боковая часть полочки – 2 детали
7. Рукав – 2 детали

INSTRUCTIONS:

1. Продублировать цельнокроеный подборт клеевой прокладкой.

2. Стачать рельефные срезы спинки, припуски заутюжить к середине и обметать. Притачать верхнюю часть спинки к нижней части, припуски заутюжить вверх и обметать.

3. Обметать внешний срез подборта. Перегнуть подборт на лицевую сторону по линии полузаноса и обтачать верхний срез до метки. Припуски у метки рассечь, вывернуть подборт на изнаночную сторону, выправить, приутюжить.

4. Стачать рельефные срезы полочки, припуски заутюжить к центру и обметать. Стачать верхнюю и нижнюю части полочки, припуски у меток рассечь, заутюжить вверх и обметать.

5. Стачать боковые срезы, припуски заутюжить на спинку и обметать. Стачать плечевые срезы, припуски разутюжить.

6. Стачать плечевые и боковые срезы внутренних верхних частей спинки и полочки, припуски разутюжить. Обметать внешний срез. Сложить внутренние детали с изделием лицевыми сторонами внутрь и обтачать срез горловины спинки и полочки и завязки. Припуски на закруглениях рассечь, в уголках высечь, вывернуть на изнаночную сторону, выправить, приутюжить. Настрочить внутреннюю часть в шов притачивания внешней части. Скрепить внешнюю и внутреннюю части по срезу проймы.

7. Стачать шов рукава, припуски приутюжить и обметать. Втачать рукава в проймы, припуски приутюжить и обметать.

8. Припуск низа платья и рукава обметать, заутюжить на изнаночную сторону и настрочить.

9. На правой полочке обметать петли, на левой полочке пришить пуговицы.

TECHNICAL DRAWING:

