# Hoodie - Sewing Pattern #4941

Recommendations on fabric: natural/mixed knit fabric of small stretchiness.



You will also need: two grommets, two cord end caps, decorative cord.

Seam allowances: all seams 1 cm.

**Note on seam allowances:**
*- If the pattern has double contour the seam allowances are included. They are 1 cm unless specified otherwise.*
*- If the pattern has single contour, the seam allowances are NOT included and need to be added when laying out the pattern.*

**Note on length of fabric:**
*Attention! The amount of fabric needed for your pattern is not included. It will depend on the selected pattern size, the width, and design of the fabric you plan to use. First, print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm). Measure how much fabric you will need. Don't forget to account for pieces that need to be cut multiple times and pieces that are cut on the fold.*

**Note on working with stretchy fabric:**
*Knitted fabric pieces are sewn together with special elastic or narrow zig-zag stitch. Seam allowance on hems can be stitched with twin needles to save stretchiness. Pieces can also be sewn together with a serger. When serging, cut seam allowances to 0.6 – 0.8 cm.*

## CUTTING:

**Note on cutting:**
*On the pattern pieces, “beam” means straight of grain. Lay out your pieces accordingly. Some pieces will be cut on the fold. This is noted on the pattern piece. Mark all notches and other design features such as pleats etc. from the pattern onto your fabric.*
*When sewing the garment, pay attention to notches, they must match up.*

Main fabric:
1. Back – cut 1 on fold
2. Center front – cut 1 on fold
3. Side front – cut 2

4. Yoke – cut 2
5. Hood – cut 4
6. Pocket welt – cut 2
7. Sleeve – cut 2
8. Cuff – cut 2
9. Placket – cut 1 on fold

## INSTRUCTIONS:

1. Fold off-set welt in half lengthwise right sides together and sew ends. Turn the piece right side out, straighten, press. Pin off-set welt onto side front according to markings and topstitch ends.

2. Sew side fronts to front, press towards center and serge.

3. Sew the yoke to sleeve, press seam allowances towards yoke and serge.

4. Sew sleeves to back, press towards the back and serge. Sew sleeves to front, press towards front and serge.

5. Sew side seams processing the sleeve seam at the same time, serge and press.

6. Sew together pieces of hood by two. Install grommets on outer hood according to the markings. Pin hoods together right sides together and sew the outer edge. Clip into curves, turn the piece right side out, straighten, press. Sew a decorative stitch along edge according to markings, making a casing. Pin right hood onto left hood and baste together along lower edge.

7. Sew hood into neckline, serge and press.

8. Sew cuff into a ring, press the seam apart. Fold cuff in half lengthwise right side out and press. Sew cuff to lower edge of sleeve, stretching it to the required length. Press towards top and serge.

9. Sew lower placket into ring, press the seam apart. Pin together lower placket in half lengthwise right side out and press. Sew lower placket to lower edge, stretching it to the required length. Press towards top and serge.

10. Thread the cord into hood, attach cord ends.

Tip: you may also use ready cuffs and knit bands for cuffs and placket.

## TECHNICAL DRAWING:

