

Dress With Wrap - Sewing Pattern #4950

Recommendations on fabric: natural/mixed fabric suitable for dresses.

You will also need: fusible interfacing, 6 buttons.

Seam allowances: seam allowance for hem of garment — 2.5 cm, other seams 1 cm.

Note on seam allowances:

- If the pattern has double contour the seam allowances are included. They are 1 cm unless specified otherwise.
- If the pattern has single contour, the seam allowances are NOT included and need to be added when laying out the pattern.

Note on length of fabric:

Attention! The amount of fabric needed for your pattern is not included. It will depend on the selected pattern size, the width, and design of the fabric you plan to use. First, print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm). Measure how much fabric you will need. Don't forget to account for pieces that need to be cut multiple times and pieces that are cut on the fold.



CUTTING:

Note on cutting:

On the pattern pieces, "beam" means straight of grain. Lay out your pieces accordingly. Some pieces will be cut on the fold. This is noted on the pattern piece. Mark all notches and other design features such as pleats etc. from the pattern onto your fabric.

When sewing the garment, pay attention to notches, they must match up.

Main fabric:

1. Upper back – cut 2
2. Back belt — cut 1
3. Lower back — cut 2
4. Front yoke — cut 4
5. Upper front — cut 2
6. Front belt — cut 2
7. Lower front — cut 2

8. Sleeve — cut 2
9. Cuff — cut 2
10. Back neck facing – cut 2
11. Front neck facing – cut 2

Fusible interfacing:

1. Cuff — cut 2
2. Back neck facing – cut 2
3. Front neck facing – cut 2

INSTRUCTIONS:

1. Apply fusible interfacing. Also apply fusible interfacing to one-piece center front facing, and to belt of front and to belt of lower front.
2. Sew darts on upper back and on lower back, press bulk towards center. Sew center seam on upper back and on lower back, press towards left and serge.
3. Sew back belt to upper part, press seam allowances towards belt and serge. Sew lower back to belt, press seam allowances towards belt and serge.
4. Sew darts on upper front and on lower front, press bulk towards center.
5. Serge inner edge of front neckline facing. Pin it to upper front right sides together and sew the neckline edge. Fold the facing onto the wrong side, straighten, press.
6. Sew a gathering stitch along upper edge of upper front and gather fullness. Pin yokes together, right sides together, insert upper front in between them and sew. Clip into curves, turn right side out yoke onto right side, press. Treat yokes as one piece in the future.
7. Sew front belt to lower front, press seam allowances towards belt and serge. Serge center edge. Pin upper front to front belt right sides together, fold away one-piece front facing onto right side, wrapping upper front and sew. Press towards belt and serge. Turn center front facing onto wrong side, press.
8. Sew side seams, press towards the back and serge.
9. Sew center seam of back neckline facing, press the seam apart. Serge lower edge. Pin back neckline facing onto self garment right sides together and sew upper edge exactly up to the marked shoulder seam line. Clip seam allowances.
10. Sew shoulder seams, placing front between back neckline facing and self back. Press seams towards back, serge. Turn pieces right side out, press. Slipstitch seam allowances of central seam of facing to the back.

11. Sew sleeve seam, press towards the back and serge. Sew a gathering stitch along sleeve cap and along lower edge and gather fullness. Sew sleeves into armholes matching notches and adjusting ease. Serge and press.
12. Sew cuff into a ring, press the seam apart. Fold cuff in half lengthwise and press right side out. Sew outer side of cuff to sleeve, fold under the seam allowance of the inner side inside and stitch-in-the-ditch along seam of outer side.
13. Serge the lower edge of garment, press onto wrong side and finish with hidden stitches.
14. Make buttonholes on right front, sew on buttons onto left front. Make an inner buttonhole on left front, sew on hidden button.

TECHNICAL DRAWING:

