# Blouse With Flounce In Princess Seam - Выкройка #4974

Recommendations on fabric: natural/mixed fabrics suitable for blouses in contrasting or similar color.

You will also need: fusible interfacing; 10 buttons.

Seam allowances: Seam allowance for hem of garment – 2.5 cm; other seams – 1 cm.



**О припусках на швы::**
*- Если на выкройке двойной контур, припуски на швы уже включены. Они составляют 1 см, если не указано иначе.*
*- Если у выкройки одинарный контур, припуски на швы не включены, и должны быть добавлены при раскрое.*

**О требуемой длине ткани:**
*Внимание! В инструкциях не указано необходимое количество ткани, так как оно зависит от ширины и рисунка ткани, а также Ваших размерных признаков. Прежде всего, распечатайте лекала и разложите их на ширине, соответствующей ширине ткани, которую Вы хотите использовать (обычно от 90 до 150 см), чтобы определить, сколько ткани Вам потребуется. Не забывайте учитывать парные детали и детали со сгибом.*

## РАСКРОЙ:

**Обратите внимание при раскрое:**
*Обратите внимание на обозначение долевой нити при раскладке деталей. Некоторые детали кроятся со сгибом. Это указано на лекале. Перенесите все отметки и другие особенности дизайна (вытачки и т.п.) с лекала на ткань.*
*При стачивании деталей, обращайте внимание на надсечки, они должны совпадать.*

Main fabric:
1. Center back yoke - cut 1
2. Side back yoke - cut 2
3. Back - cut 1 on fold
4. Center front - cut 2
5. Side front - cut 2
6. Sleeve – cut 2
7. Flounce — cut 2

Decorative fabric:
1. Placket — cut 2
2. Stand collar – cut 2
3. Cuff – cut 2

Fusible interfacing:
1. Placket — cut 2
2. Stand collar – cut 1
3. Cuff – cut 2

## Инструкции:

1. Apply fusible interfacing.

2. Pin stand collars together right sides together and sew outer edges. Start and stop sewing exactly at the marked line of seam. Clip into curves. Turn the finished stand collar right side out and press.

3. Press placket in half lengthwise right side out. Sew outer edge of placket to center front, press seam allowances onto placket. Fold the edge of inner placket under and stitch in the ditch.

4. Sew shoulder seams of centre front and center back yoke, press towards the back and serge. Sew shoulder seams of side front and side back yoke, press towards the back and serge.

5. Sew a baby hem or thin rolled hem along the outer edge of flounce. Sew princess seam on front and back yoke (sew center pieces to side pieces), inserting the flounce between the pieces. Serge seams and press towards center.

6. Sew yoke to back, press seam allowances towards yoke and serge.

7. Sew side seams, press towards the back and serge.

8. Sew outer stand collar into neckline, press seam allowances at stand collar. Turn under the unfinished edge of inner stand collar and stitch in the ditch.

9. Serge the sleeve edges separately. Sew sleeve seam from armhole up to mark for slit, press the seam apart. Topstitch slit at 0.1 cm from fold. Sew sleeves into armholes, serge and press.

10. Fold cuff in half lengthwise, right sides together and sew side seams. Turn the piece right side out, press. Sew outer side of cuff to sleeve, fold the seam allowance of the inner cuff inward and stitch in the seam attaching the outer cuff.

11. Turn hem under inside at 1 cm, then at 1.5 cm and topstitch.

12. Make buttonholes on right placket and on stand collar, sew on buttons on the left one. Make buttonholes and sew on buttons onto cuffs.

**Технический рисунок:**

