

Knit Pullover With Raglan Sleeve - Sewing Pattern #4986

Recommendations on fabric: natural/mixed knit fabric of small stretchiness in similar or contrasting colours.

Seam allowances: Seam allowance for hem – 2.0 cm. Other seams – 0.7 cm.

Note on seam allowances:

- If the pattern has double contour the seam allowances are included. They are 1 cm unless specified otherwise.
- If the pattern has single contour, the seam allowances are NOT included and need to be added when laying out the pattern.

Note on length of fabric:

Attention! The amount of fabric needed for your pattern is not included. It will depend on the selected pattern size, the width, and design of the fabric you plan to use. First, print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm). Measure how much fabric you will need. Don't forget to account for pieces that need to be cut multiple times and pieces that are cut on the fold.



CUTTING:

Note on cutting:

On the pattern pieces, "beam" means straight of grain. Lay out your pieces accordingly. Some pieces will be cut on the fold. This is noted on the pattern piece. Mark all notches and other design features such as pleats etc. from the pattern onto your fabric.

When sewing the garment, pay attention to notches, they must match up.

Main fabric 1:

1. Center back - cut 2
2. Center front - cut 1 on fold
3. Sleeve - cut 2

Main fabric 2:

1. Side back - cut 2
2. Side front - cut 2

3. Facing — cut 2
4. Cuff - cut 2

INSTRUCTIONS:

1. Sew side backs to center back. Sew side fronts to center front, press towards center and serge.
2. Sew center back seam, press towards left and serge.
3. Sew sleeve to back, press seam allowances towards sleeve and serge. Sew sleeve to front, press seam allowances towards sleeve and serge.
4. Sew side seam and sleeve seam at the same time, serge and press.
5. Sew cuff into a ring, press seam apart. Fold cuff in half lengthwise, wrong sides together, and sew to lower edge of sleeve, serge.
6. Sew each facing into a ring, press seam apart. Pin together facings right sides together and sew the neckline. Clip into curves, turn the piece right side out, straighten, press. Sew neckline facing into neckline, serge and press.
7. Serge bottom edge of garment, press onto wrong side and topstitch.

Make sure that the head passes through the neckline opening before sewing the center back seam. Otherwise, make a closure: sew center back edge stopping at 5-6 cm before the neckline edge, make a loop buttonhole, sew edge of neckline and ends of facings, inserting the loop buttonhole, sew facing to neckline, sew on button..

TECHNICAL DRAWING:

