Hat - Sewing Pattern #5575



Attention! Please provide the full girth of the head, measured across most protruding areas across center of front and protrusions at the nape (size 48).

Fabric recommendations: eco leather, coat fabrics.

You will also need: lining.

Seam allowances: all seams 1 cm, all edges of tube - 0 cm.

Note on seam allowances:
- If the pattern has double contour the seam allowances are included. They are 1 cm unless specified otherwise.
- If the pattern has single contour, the seam allowances are NOT included and need to be added when laying out the pattern.

Note on length of fabric:
Attention! The amount of fabric needed for your pattern is not included. It will depend on the selected pattern size, the width, and design of the fabric you plan to use. First, print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm). Measure how much fabric you will need. Don't forget to account for pieces that need to be cut multiple times and pieces that are cut on the fold.

CUTTING:

Note on cutting:
On the pattern pieces, “beam” means straight of grain. Lay out your pieces accordingly. Some pieces will be cut on the fold. This is noted on the pattern piece. Mark all notches and other design features such as pleats etc. from the pattern onto your fabric.
When sewing the garment, pay attention to notches, they must match up.

Self fabric:

1. Gore - cut 6
2. Band (okolysh) - cut 1
3. Tube (trubochka) - cut 1

Lining:

1. Gore - cut 6

2. Bias trimming - cut 1

INSTRUCTIONS:

1. Sew gores together by two, right sides together. Sew one more gore to each pair of gores.

2. Fold longer edges of tube under onto the wrong side, matching the center, fold in half lengthwise, and topstitch at 0.1. - 0.2. cm from the edge.

3. Baste tube to one of the halves of the cap. Fold gores together, matching them exactly at the center, and sew central seam, sewing the tube at the same time.

4. Sew lining in the same way as the self. Place lining inside the cap, slipstitch lining to self along the seams.

5. Sew band into a ring, press apart and topstitch seam allowances on both sides of the seam. Fold band in half lengthwise wrong side together and topstitch lengthwise, making parallel stitches at 0.5 - 0.6 cm from each other.

6. Pin band to cap right sides together, baste band to cap, adjusting ease. Pin bias trimming cut of lining from the band side. Sew. Fold bias trimming onto wrong side, fold under and stitch in the ditch.

TECHNICAL DRAWING:

