Tunic Dress - Sewing Pattern #5971



Recommendations on fabric: natural/mixed knit fabric of small/medium stretchiness.

Seam allowances: seam allowance for hem of garment – 1.5, other seams 0.8 cm.

Note on seam allowances:
- If the pattern has double contour the seam allowances are included. They are 1 cm unless specified otherwise.
- If the pattern has single contour, the seam allowances are NOT included and need to be added when laying out the pattern.

Note on length of fabric:
Attention! The amount of fabric needed for your pattern is not included. It will depend on the selected pattern size, the width, and design of the fabric you plan to use. First, print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm). Measure how much fabric you will need. Don't forget to account for pieces that need to be cut multiple times and pieces that are cut on the fold.

Note on working with stretchy fabric:
Knitted fabric pieces are sewn together with special elastic or narrow zig-zag stitch. Seam allowance on hems can be stitched with twin needles to save stretchiness. Pieces can also be sewn together with a serger. When serging, cut seam allowances to 0.6 – 0.8 cm.

CUTTING:

Note on cutting:
On the pattern pieces, “beam” means straight of grain. Lay out your pieces accordingly. Some pieces will be cut on the fold. This is noted on the pattern piece. Mark all notches and other design features such as pleats etc. from the pattern onto your fabric.
When sewing the garment, pay attention to notches, they must match up.

Tela principal:
1. Delantero – 1 pieza en pliegue
2. Espalda – 2 piezas
3. Manga – 2 piezas
4. Puño – 2 piezas
5. Vista del escote delantero – 1 pieza
6. Vista del escote trasero – 1 pieza

La entretela adhesiva:

1. Vista del escote delantero – 1 pieza
2. Vista del escote trasero – 1 pieza

INSTRUCTIONS:

1. Aplicar adhesivo entretela a la vista de escote.

2. Coser la costura trasera central. Planchar los márgenes de costura hacia la izquierda y rematar.

3. Hacer tres pliegues dobles en el delantero. Hilvanarlos a lo largo del borde superior.

4. Coser las costuras de los hombros y las costuras laterales. Planchar las costuras hacia atrás y rematar.

5. Coser las costuras de los hombros de las vistas del escote. Planchar la costura abierta. Rematar el borde exterior de las vistas. Coser vista al escote. Doblar la vista hacia adentro y planchar. Cosa a mano la vista a los márgenes de costura cerca de la costura trasera central y las costuras de los hombros.

6. Coser las costuras de las mangas. Rematar los márgenes de costura y planchar. Coser una línea de puntada en el borde inferior de la manga со слабо затянутыми стежками y hacer fruncidos. Coser el puño en un anillo. Doblar el puño por la mitad a lo largo por el revés y planchar. Coser el puño a la manga.

7. Coser las mangas en las sisas haciendo coincidir las marcas y ajustando la tela. Rematar y planchar.

8. Rematar el borde inferior de la prenda. Doblar por el lado revés, planchar y pespuntear.

TECHNICAL DRAWING:

