

Wind Jacket - Sewing Pattern #7153

Recommendations on fabric: whipcord (polyester, cotton, mixed fabric); lining.

You will also need: fusible interfacing; 1 separable zipper (the length is equal to garment front's length including stand collar); elastic cord for hood; 2 caps for cord; trim cord.

Seam Allowances: hem of garment and hem of sleeves – 4.5 cm, hem of lining details and button stands – 0cm (lining comes to the hem turnup), other seams 1 cm.



Note on seam allowances:

- If the pattern has double contour the seam allowances are included. They are 1 cm unless specified otherwise.
- If the pattern has single contour, the seam allowances are NOT included and need to be added when laying out the pattern.

Note on length of fabric:

Attention! The amount of fabric needed for your pattern is not included. It will depend on the selected pattern size, the width, and design of the fabric you plan to use. First, print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm). Measure how much fabric you will need. Don't forget to account for pieces that need to be cut multiple times and pieces that are cut on the fold.

CUTTING:

Note on cutting:

On the pattern pieces, "beam" means straight of grain. Lay out your pieces accordingly. Some pieces will be cut on the fold. This is noted on the pattern piece. Mark all notches and other design features such as pleats etc. from the pattern onto your fabric.

When sewing the garment, pay attention to notches, they must match up.

Main fabric:

1. Front - cut 2
2. Back - cut 1
3. Sleeve inset — cut 2
4. Sleeve — cut 4
5. Hood - cut 2
6. Center part of hood – cut 1
7. Hood facing – cut 1
8. Buttonstand - cut 2

9. Big sacking - cut 2
10. Off-set welt - cut 2
11. Off-set welt of inner pocket - cut 1

Cut bias tapes from main fabric of 3.5 cm wide for trimming. The length of tapes depends on trim cord length. Attention! After making a trim cord there should be left 1 cm seam allowance. Otherwise you will need to regulate yourselves the width of tapes.

Lining:

1. Front - cut 2
2. Back - cut 1
3. Sleeve - cut 2
4. Small sacking - cut 2
5. Hood - cut 2
6. Center part of hood - cut 1
7. Big sacking of inner pocket - cut 1
8. Small sacking of inner pocket - cut 1

INSTRUCTIONS:

1. Making trim cords. Sew bias tapes together, press seams. Fold given tape in half, set the cord in and stitch along the contour.

2. Welt pockets. Apply fusible interfacing to the welt, fold in half lengthwise, press. Apply fusible interfacing to pocket location. Mark a line on the welt. This line will determine the width of ready off-set welt. Stitch trim cord onto outer side of the welt. Stitch small sacking onto inner side. Place welt with sacking onto right side of front, matching marking line on pocket with the line on the welt. Outer side of the welt should match the right side of the front. Sew the welt. Stitch big sacking to upper marking line on the pocket. Slit pocket opening in center between marking lines, making slashes to corners. Turn pockets details wrong side out. Straighten and press seam allowances. Sew edges of sackings, fastening the corners of pocket. Edges of sackings should go into zipper connecting seam and come up to hem line.

3. Main fabric details. Sew sleeves to back and fronts. Put fastening stitch on the armhole. Sew sleeve inset to given details, inserting a trim cord. Stitch. Sew side and sleeve seams. Sew parts of hood. Stitch along the seams on central part. Sew hood into neckline. Serge holes on the hood as marked.

4. Inner pocket. Apply fusible interfacing to the welt, fold in half lengthwise, press. Mark a line on welt. This line will determine the width of ready off-set welt. Stitch small sacking onto inner side. Place welt with sacking onto right side of front lining, matching the line of pocket marking with the line on the welt. Outer side of the welt should match the right side of lining. Sew the welt. Sew big sacking to upper marking line on pocket. Slit pocket opening in center between marking lines, making slashes to corners. Another side of the pocket comes into button stands connecting seam. Turn pockets details wrong side out. Straighten and press seam allowances.

Sew edges of sackings, fastening pocket corner from one side.

5. Lining. Sew button stand to front lining. Sew lining details, stitching sleeve into open armhole. Sew parts of hood lining and connect to hood facing. Sew hood lining into neckline of lining details.

6. Zipper. Place half of zipper to front band edge right sides together (zipper blades are directed from the front band). Overstitch edges of front bands and hood with lining, sewing in the zipper at the same time. Turn the garment right side out.

7. Press hems. Turn first at 1 cm, then again at 3 cm. Topstitch hems.

8. Make a fastening stitch along front bands and the hood.

9. Press ready jacket.

10. Set cord into the hood.

TECHNICAL DRAWING:

